



SINGLE-SPINDLE **ROTARY CUTTERS**

FEATURES

Ideal for tractors 15 – 50 hp

3-point hitch: Limited CAT 1
& CAT 1

Quick change pins

3-year limited gearbox
warranty

Quickly cut down weeds, brush and your list of chores.

Whether you're clearing brush along miles of fence line, maintaining a roadway or just keeping weeds in check in an orchard or on a large property, these single-spindle rotary cutters sized for compact tractors help you make short work of anything that's growing where you don't want it to. Each features a rugged frame, a smooth, slope-top deck and quick-change blades built to easily handle the toughest conditions.

INNOVATIVE DESIGN AND TECHNOLOGY



FULL-LENGTH SKID SHOES

are a standard feature, allowing cutter to glide easily over rough terrain.



OPTIONAL CHAIN SHIELDING



Yanmar Single-Spindle Rotary Cutter Specifications

VEGETATION MANAGEMENT

MODEL	LOW-HP DUTY				STANDARD DUTY			
	YRC42	YRC48	YRC60	YRC72	YRC480	YRC600	YRC720	YRC840
Tractor PTO HP	12	15	18	21	15-50	25-50	30-65	35-90
Hitch Cat. / Type	Cat1/clevis				Cat1 / clevis			Cat1&2
Cutting Width (in.)	42	48	60	72	48	60	72	84
Transport Width (in.)	-	53.5	65.5	72.5	53.5	65.5	72.5	89.5
Maximum Overall Length (in.)	-	92	104	116	92	104	116	128
Deck Length (in.)	-	58	70	84	58	70	84	96
Cutting height range (in.)	2-9"				1-9"			
Cutting Capacity (in.)	1"				1.5"	2"		
Gearbox HP	50hp				65	75	90	
Gearbox output shaft diameter (in.)	-	1.57			1.57			2
Blade tip speed (fpm)	11,460	13,100	13,620	14,340	13,000	14,355	14,963	15,086
Deck side depth (in.)	7"				9.4"	9.5"		
Approximate Weight* (lbs.)	360	410	494	575	498	604	828	1084
Blade dimensions (in.)	0.5 x 3				(2) 0.38 x 3			(2) 0.5 x 3
Blade carrier	Oval stump jumper				Oval stump jumper			Round
Blade mount system	Quick change pins				Quick change pins			
Blade pin diameter (in.)	1.5				1.5			
Cutting deck thickness	11-Gauge				10-Gauge			
Safety-shielded driveline	Cat 3				Cat 3			Cat 4
Driveline protection	shear-pin or slip-clutch	shear-pin or slip-clutch	shear-pin or slip-clutch	slip-clutch	shear-pin or slip-clutch		slip-clutch	
Frame & Deck Support	3/8" rails				formed channel	3 x 4" full length structural beams		
Tail Wheel	4 x 16 laminated				4 x 16 laminated			
PTO Speed (RPM)	540				540			
Quick Hitch Compatible	Yes				Yes			
Cutting Area Shielding	belt standard / Chain shielding optional				belt standard / Chain shielding optional			

©2016 Yanmar America Corporation. YT16-406

Yanmar has a corporate policy of continuous product improvement and development; therefore, data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manuals. Before operating a machine, read, understand, and follow all instructions in the manual and on the machine. Yanmar disclaims all representations, express or implied, or any liability from the use of this publication.

YANMAR

To learn more or to find a dealer nearest you, please visit YanmarTractor.com.